

Concentrating on audio since 1988

MP120B 120W Mixer Amplifier with USB





- ➤ Built in USB player
- ➤ 4 microphones input, 2 auxiliary inputs and 1 line output
- Mic 1 input has the highest priority level muting function
- > Individual volume control for all inputs
- > Treble and Bass control
- Siren trigger when short circuit, overload or overheat is detected

Description

MP120B mixer amplifier has a wide range of output power ratings and enhanced cost effectiveness with this model: 120W. The mixer amplifier is integrated with a USB player for MP3 playback. It is design to work with high impedance (100V) speaker system. The 5-segments LED output meter is to monitor the output signal level. It is standard 19" rack-mountable with earpieces provided and only takes up to 2U of space.

Specification


Model	MP60B	MP120B
Rated	60W	120W
Output Regulation	Less than 3dB	
Speaker Output	100V	
AUX Output	1V	
Input Sensitivity	Mic 1, 2, 3, 4 : 3mV (±0.5mV) Unbalanced	
	Line 1, 2 : 200mV (±30mV) Unbalanced	
Frequency Response	65Hz – 20kHz (±3dB)	
Distortion	Less than 1% at 1kHz, 1/3 rated output voltage	
S/N Ration	Mic 1, 2, 3, 4 : Bigger than 80dB	
MP3 Input Sensitivity	230 – 280mV	
Muting Function	Mic 1 overrides other input signals with 0 to -30dB attenuation	
Protection	AC Fuse, DC Voltage, overload and short circuit	
Power Requirement	AC 220-240V / 50-60Hz	
Power Consumption	90W	200W
Dimension (W × H × D)	430 × 300 × 88mm (2U)	
Net Weight	9 kg	7kg
Gross Weight	6 kg	10kg

1



Front Panel

Concentrating on audio since 1988



- Power switch (power indicator lighting as ON state)
 For main power.
- 2. LED power indicator For main power.
- 3. LED level meter Indicate output level.
- 4. Bass control

Adjust bass response.

- 5. Treble control
- Adjust treble response.
- 6. MP3 output volume control Adjust treble response.


- 7. Line volume control Adjust Line input volume.
- 8. Mic1-Mic4 volume control Adjust microphone volume.
- 9. Mic1 input jack

Connect to microphone of unbalanced 30-600 Ω with 1/4"phone plug. The muting

function is activated while the signal is sent to Mic1.

- 10. MP3 Display
- 11. MP3 USB input jack
- 12. MP3 Player control button

Rear panel



- 1. Mute control
- Adjust muting function.
- 2.2. Line 1 input and Line 2 input Connect to linear source equipment.
- 3. Line output

Connect a recorder

4. Fan Exhaust Window

- 5. Speaker output 100V
- 6. AC fuse

Prevent the excessive AC

7. AC power Input jack

Connect to AC power sou

8. Mic2-Mic4 input jack