

DSP224N IP Network Wall Mount Speaker



Features

- Clearly output of the origin sound.
- Built-in high-capacity memory, built-in program source, with timer / file saving function.
- Able to operate independently from the network and the host.
- You can play background music from the host system, emergency paging, alarm signals, and so on.
- 10 / 100M adaptive, DHCP / static IP support, LAN and WAN support.
- Main and sub-box, stereo design.
- Made of high quality fiberboard, birch and cold pressed leather so as to effectively prevent resonant sound.

Description

IP Network wall speaker is made of high quality crimson birch, classic and elegant. The output sound is clear, bright and thorough. Net cover is designed arc shape, elegant and beautiful.

Specification

Project	Specification	Parameter	
Acoustic System	Speaker Unit	6.5"×2 , 3"×1	
	Sensitivity (1m,1W)	91±2dB	
	Maximum Sound Pressure Level (1m)	103±2dB	
	Frequency Response	100Hz-16kHz	
Power Amplifier System	Power Amplifier	Rated Power (RMS)	2×20W
		Frequency Response	20Hz-20KHz
		Signal to Noise Ratio	≥81dB
		Distortion	≤0.1%
		Channel Separation	> 60dB
	LINE Input	Input Resistance	> 10kΩ
		Sensitivity	1.0V
	Audio	Decoding Format	MP3, WMA, WAV, ACC, OGG, APE, FLAC etc
Other Specifications	Network Interface	RJ45 (10/100M)	
	Supporting Agreement	TCP/IP、 UDP、 ICMP、 IGMP (Multicast)	
	Power Input	~90-240V 50Hz/60Hz 1A	
	Product Size (High × Width × Depth)	510×200×125mm	
	Weight	4.4kg	